

Contents

Acknowledgments	i
Abstract	iii
List of Figures	ix
List of Tables	xiii
List of Abbreviations	xv
List of Symbols	xvii
1 Background	1
1.1 Large ground-based observatories	1
1.2 Vibration isolation	4
1.2.1 Passive isolation strategy	5
1.2.2 Active isolation strategy	8
1.3 Contributions	13
1.4 Thesis overview	14
2 Inertial sensor	15
2.1 Passive inertial sensor	15
2.2 Active inertial sensor	21
2.3 Conclusion	24
3 Inertial sensor readout	27
3.1 Readout mechanism	28
3.1.1 Inductive readout	28
3.1.2 Capacitive readout	29
3.1.3 Optical linear encoder	30
3.1.4 Michelson interferometric readout	31
3.1.5 Comparison	33
3.2 Long-range interferometric readout	34
3.2.1 Polarisation state based readout	34
3.2.2 Transverse electromagnetic mode based readout	37
3.2.3 Prototype of long-range compact interferometric readout	37
3.3 Prototype modelling	40
3.4 Data processing	45

3.4.1	Normalisation	46
3.4.2	Ellipse fitting	47
3.5	Experimental validation	50
3.5.1	Working principle validation	50
3.5.2	Resolution characterisation	54
3.6	Conclusion	56
4	Inertial sensor mechanics	57
4.1	Flexure joint	58
4.1.1	Clamped-plate hinge	58
4.1.2	Cross-spring hinge	61
4.1.3	Notch hinge	63
4.1.4	Spiral flexure	65
4.1.5	Comparison	66
4.2	HINS mechanics	68
4.2.1	Modelling	69
4.2.2	Experimental characterisation	79
4.3	VINS mechanics	81
4.3.1	Modelling	82
4.3.2	Experimental characterisation	88
4.4	Assembly of inertial unit	89
4.5	Conclusion	90
5	Inertial sensor characterisation	93
5.1	Inertial sensor modelling	93
5.2	Noise sources	97
5.2.1	Data acquisition system noise	98
5.2.2	Photodetector noise	100
5.2.3	Laser noise	105
5.2.4	Mechanics noise	111
5.2.5	Ambient noise	113
5.3	Noise budgeting	113
5.3.1	Interferometric readout	114
5.3.2	Inertial sensor	115
5.4	Conclusion	118
6	Huddle test	119
6.1	Working principle	119
6.2	Experimental result	121
6.2.1	Result of the HINS	122
6.2.2	Result of the VINS	123
6.3	Discussion	124
6.3.1	Influence of input level	126
6.3.2	Influence of parameter estimation	127
6.3.3	Influence of incoherent excitations	129
6.4	Conclusion	132
7	Summary and future work	133
7.1	Summary	133

7.2	Suggestions for future research	135
A	Liquid absolute tilt-meter (LAT)	137
A.1	Working principle	137
A.2	Four-quadrature photodetector (Quad-PD)	139
A.3	Resolution estimation	140
B	Polarisation	143
C	Phase tracking	147
D	Optical components list	149
E	Laser specification	151
F	Vacuum system	153
G	Key original script	157
G.1	Interferometric readout simulation	157
G.2	$1/f$ noise generator	160
G.3	Phase noise generator	161
G.4	Intensity noise generator	161
G.5	Ground motion generator	162
	Bibliography	163