

# Table of Contents

<b>List of Figures</b>	<b>v</b>
<b>List of Tables</b>	<b>viii</b>
<b>List of Acronyms</b>	<b>ix</b>
<b>1 Introduction</b>	<b>1</b>
1.1 Background . . . . .	1
1.2 SDNoC integration within chiplet-based systems . . . . .	5
1.3 SDNoC integration within CoC . . . . .	7
1.4 Security Challenges . . . . .	7
1.5 Objective-Contributions . . . . .	8
1.6 Publications . . . . .	9
1.7 Thesis Organization . . . . .	10
<b>2 Network-on-Chip Design</b>	<b>11</b>
2.1 Introduction . . . . .	11
2.2 NoC Architecture . . . . .	12
2.3 NoC topologies . . . . .	14
2.4 NoC Routing . . . . .	17
2.4.1 Routing Problems . . . . .	20
2.4.1.1 Deadlock . . . . .	20
2.4.1.2 Livelock . . . . .	20
2.4.1.3 Starvation . . . . .	21
2.5 Flow Control . . . . .	21
2.6 Overview of Academic and Commercial NoCs . . . . .	22
2.7 NoC challenges . . . . .	24
2.7.1 Quality of Service . . . . .	24
2.7.2 Latency . . . . .	25
2.7.3 Security . . . . .	25
2.8 Summary-Discussion . . . . .	27

<b>3</b>	<b>Software Defined Network-on-Chip</b>	<b>29</b>
3.1	Introduction . . . . .	29
3.2	Software Defined Network . . . . .	30
3.2.1	Security Issues . . . . .	31
3.3	State of the art . . . . .	33
3.3.1	Literature . . . . .	33
3.3.2	Discussion . . . . .	36
3.4	SDNoC Architecture . . . . .	37
3.5	Routing within SDNoC . . . . .	40
3.5.1	XY Routing . . . . .	41
3.5.2	West First Routing . . . . .	41
3.5.3	North Last Routing . . . . .	42
3.5.4	Negative First Routing . . . . .	42
3.5.5	Odd Even Routing . . . . .	42
3.5.6	Modified Odd Even (OESL) . . . . .	43
3.6	MicroLET Protocol . . . . .	45
3.6.1	Packet format . . . . .	45
3.6.2	Network Messages . . . . .	46
3.6.3	Communication Protocol Phases . . . . .	46
3.7	Summary-Discussion . . . . .	48
<b>4</b>	<b>Implementation and Evaluation of SDNoC</b>	<b>51</b>
4.1	Introduction . . . . .	51
4.2	NoC Simulators . . . . .	52
4.3	Implementation of SDNoC prototype . . . . .	53
4.3.1	SDNoC Parameters . . . . .	55
4.3.1.1	Impact of $\tau$ . . . . .	57
4.3.2	MicroLET . . . . .	58
4.4	Routing Algorithms . . . . .	59
4.4.1	Standard Deviation Coverage . . . . .	64
4.5	Analysis of variances . . . . .	69
4.5.1	Background . . . . .	69
4.5.2	Scenarios-Results . . . . .	73
4.5.3	One-way ANOVA . . . . .	74
4.5.3.1	N-way ANOVA . . . . .	80
4.6	Summary-Discussion . . . . .	83
<b>5</b>	<b>Security within SDNoC</b>	<b>85</b>
5.1	Introduction . . . . .	85
5.2	Secure Sdn-based Protocol over mpSoC . . . . .	87
5.2.1	Security Requirements . . . . .	87
5.2.1.1	Phase 1 . . . . .	88

5.2.1.2	Phase 2 . . . . .	88
5.2.2	Group Key Agreement . . . . .	89
5.2.2.1	Assumptions . . . . .	89
5.2.2.2	Group Key Agreement Protocols . . . . .	89
5.2.3	Communication Protocol . . . . .	92
5.2.3.1	Network Architecture . . . . .	92
5.2.3.2	Packet Format . . . . .	92
5.2.3.3	Network Messages . . . . .	92
5.2.3.4	SSPSoC Network Initialization . . . . .	94
5.3	Byzantine Faults . . . . .	97
5.3.1	Related Work . . . . .	98
5.3.2	Fault Model . . . . .	99
5.3.3	Algorithm . . . . .	100
5.3.3.1	Normal Case Operation . . . . .	100
5.3.3.2	Byzantine fault Case Operation . . . . .	102
5.4	Hardware Trojan-Greyhole attack . . . . .	104
5.4.1	Related work . . . . .	106
5.4.2	Launching of HT-Greyhole Attack . . . . .	107
5.4.3	Detection . . . . .	111
5.4.4	Defense . . . . .	112
5.5	Summary . . . . .	113
<b>6</b>	<b>Implementation and Evaluation of security within SDNoC</b>	<b>115</b>
6.1	Introduction . . . . .	115
6.2	Secure Sdn-based Protocol over mpSoC . . . . .	115
6.2.1	Implementation and Performance Analysis . . . . .	115
6.2.1.1	Network Performance . . . . .	117
6.2.1.2	Memory Usage . . . . .	118
6.2.2	Conclusion . . . . .	120
6.3	Byzantine Faults . . . . .	121
6.3.1	Implementation . . . . .	121
6.3.2	Evaluation . . . . .	121
6.3.3	Conclusion . . . . .	123
6.4	Hardware Trojan-Greyhole attack . . . . .	125
6.4.1	Evaluation of the Detection Strategy . . . . .	125
6.4.1.1	Background . . . . .	125
6.4.1.2	Test Cases . . . . .	128
6.4.2	Conclusion . . . . .	135
6.5	Summary-Discussion . . . . .	135
<b>7</b>	<b>Conclusion</b>	<b>137</b>
7.1	Future Work . . . . .	140

<b>A GEM5 Code</b>	<b>145</b>
<b>Bibliography</b>	<b>212</b>

# List of Figures

1.1	Chiplet-based System . . . . .	2
1.2	Cloud-of-Chips Platform Architecture . . . . .	3
1.3	History of interconnect technology: From Bus to NoC . . . . .	5
1.4	SDNoC architecture within a chiplet . . . . .	6
2.1	System composition categorization along the axes of homogeneity and granularity of system components [Bjerregaard and Mahadevan, 2006] . . . . .	12
2.2	NoC architecture . . . . .	13
2.3	NoC architecture: a) Mesh, b) Torus. . . . .	15
2.4	NoC architecture: a) Ring b) Star. . . . .	16
2.5	NoC architecture: a) Tree b) Butterfly. . . . .	16
2.6	Routing levels in NoC . . . . .	17
3.1	SDN Architecture . . . . .	31
3.2	NoC vs SDNoC architecture. . . . .	37
3.3	SDNoC architecture. . . . .	38
3.4	SDNoC router architecture. . . . .	39
3.5	(a) XY. (b) Negative-First. (c) West-First. (d) North-Last. The solid red lines indicate the non-valid turns and the dashed lines indicated the valid turns. . . . .	42
3.6	Odd-Even Routing . . . . .	43
3.7	Packet format . . . . .	46
4.1	Modified and Added files tree . . . . .	54
4.2	Source and destination under Transpose and BitReverse traffic . . . . .	56
4.3	Average latency of Transpose traffic under different traffic injection rates (Topology:8x8). . . . .	57
4.4	Impact of $\tau$ on the average latency and throughput ( $t_{ir} = 0.02$ ). . . . .	58

4.5	Performance measurements under Uniform traffic (Topology: 2x2 Mesh).	60
4.6	Performance measurements under Uniform traffic (Topology: 4x4 Mesh).	60
4.7	Performance measurements under Uniform traffic (Topology: 8x8 Mesh).	61
4.8	Performance measurements under BitReverse traffic (Topology: 2x2 Mesh)	61
4.9	Performance measurements under BitReverse traffic (Topology: 4x4 Mesh)	62
4.10	Performance measurements under BitReverse traffic (Topology: 8x8 Mesh)	62
4.11	Performance measurements under Transpose traffic (Topology: 2x2 Mesh)	63
4.12	Performance measurements under Transpose traffic (Topology: 4x4 Mesh)	63
4.13	Performance measurements under Transpose traffic (Topology: 8x8 Mesh)	63
4.14	95% coverage of mean values under Uniform traffic (Topology: 2x2 Mesh).	66
4.15	95% coverage of mean values under Uniform traffic (Topology: 4x4 Mesh).	66
4.16	95% coverage of mean values under Uniform traffic (Topology: 8x8 Mesh).	66
4.17	95% coverage of mean values under Bit Reverse traffic (Topology: 2x2 Mesh).	67
4.18	95% coverage of mean values under Bit Reverse traffic (Topology: 4x4 Mesh).	67
4.19	95% coverage of mean values under Bit Reverse traffic (Topology: 8x8 Mesh).	67
4.20	95% coverage of mean values under Transpose traffic (Topology: 2x2 Mesh).	68
4.21	95% coverage of mean values under Transpose traffic (Topology: 4x4 Mesh).	68
4.22	95% coverage of mean values under Transpose traffic (Topology: 8x8 Mesh).	69
4.23	Graphical representation of the power of rejection of the null hypothesis.	74
4.24	One-way Anova boxplot	76
4.25	One-way Anova boxplot	77
4.26	Multiple comparison of the mean latency of routing, traffic, tir	78

4.27	Multiple comparison of the mean throughput of routing, traffic, tir . . . . .	79
5.1	Packet format [Ellinidou et al., 2018] . . . . .	93
5.2	Private Key exchange . . . . .	95
5.3	SSPSoC message layer. . . . .	96
5.4	Messages under Normal Case operation . . . . .	102
5.5	HT-Greyhole . . . . .	108
5.6	HT-Greyhole router. . . . .	109
5.7	HT design on circuit level. . . . .	110
6.1	Performance results of SSPSoC protocol . . . . .	119
6.2	Memory usage of two GKA protocols . . . . .	120
6.3	Normal Case Operation Scenario measurements. . . . .	122
6.4	Byzantine fault case operation scenarios measurements. . . . .	124
6.5	ROC space and plots of five discrete classifier [Fawcett, 2006].	127
6.6	Roc curve diagrams for 1, 3, 6 HT-Greyhole routers with tv=0, -10, -100 and for Transpose, BitReverse, Uniform traffic.	131
6.7	1 HT-Greyhole router under different traffic scenarios. . . . .	133
6.8	1, 3, 6 HT-Greyhole routers scenarios measurements. . . . .	134

# List of Tables

3.1	Routing algorithms implemented within SDNoC . . . . .	41
3.2	Designed Network messages . . . . .	47
4.1	NoC Simulators . . . . .	52
4.2	Possible outcomes after decision process within ANOVA . .	73
4.3	One way ANOVA . . . . .	75
4.4	Results of N-way ANOVA for latency and throughput . . .	82
5.1	Designed Network messages . . . . .	93
5.2	Designed Network messages . . . . .	101
6.1	Packet loss improvement. . . . .	123
6.2	Confusion Matrix . . . . .	126
6.3	Measures for binary classification . . . . .	127
6.4	Results of binary classification for detection algorithm . . .	129
6.5	Packet loss improvement with defense method. . . . .	134
7.1	STRIDE Model analysis for SDN and SDNoC . . . . .	142